



EVERKEM  
FLAME RETARDANTS & ADDITIVES

**PRODUCT GUIDE**  
ANTIOXIDANTS  
UV STABILIZERS  
BLOWING AGENTS  
OTHERS

[everkem.com](http://everkem.com)

# “WHO WE ARE,”

## EVERKEM is leader in the distribution of chemical additives since thirty years

WITH A CONTINUOUS EXPANSION OF ITS BUSINESS WORLDWIDE, FROM EUROPE TO TURKEY TO BOTH NORTH AND SOUTH AMERICA.











We are specialized in flame retardants, while our portfolio includes also Antioxidants, UV Adsorbers, Blowing agents, Titanium Dioxide, etc. With two warehouses, respectively of 1'500 and of over 10'000 square meters, we are ready to promptly satisfy every requests from our customers. Lastly, our head office in Milan (Italy) hosts 70 square meters of analytical laboratory, which allows EVERKEM to always provide high-quality materials.

EVERKEM commercial headquarter is located in Milan, the thriving economic capital of Italy, whereas the administrative office and the 1'500 m<sup>2</sup> warehouse (equipped to store up to 1'000 MT of liquid additives) are close to Ravenna's port. The second storage facility is strategically located in the northern part of Milano province and another one dedicated to ADR products is being established near Lodi.







## 1. LIGHT STABILIZERS



### 1.1 BENZOTRIAZOLES

BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVERSTAB P		2-(2H-benzotriazol-2-yl)-4-methylphenol CAS: 2440-22-4 Molecular Formula: C <sub>13</sub> H <sub>11</sub> N <sub>3</sub> O Purity: ≥ 99% Molecular Weight: 225.25 g/mol		Melting range 128 - 133 °C	PVC, PS, PC, PMMA, AS Resin, ABS Resin, PP, PE
EVERSTAB 234		2-(2H-benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol CAS: 70321-86-7 Molecular Formula: C <sub>30</sub> H <sub>29</sub> N <sub>3</sub> O Purity: ≥ 99% Molecular Weight: 447.57 g/mol		Melting range 137 - 141 °C	PBT, PET, POM Copolymer, PC, PC/ABS, TPE, TPU, PA, PES
EVERSTAB 326		2-(2-Hydroxy-3'-tert-butyl-5'-methylphenyl)-5-chloro benzotriazole CAS: 3896-11-5 Molecular Formula: C <sub>17</sub> H <sub>18</sub> ClN <sub>3</sub> O Purity: ≥ 99% Molecular Weight: 315.8 g/mol		Melting range 137 - 142 °C	Polyolefins, Unsaturated Polyester Resins (normal and chlorinated), Elastomers and Adhesives, Cosmetic Products
EVERSTAB 329		2-(2-Hydroxy-5-tert-octylphenyl) benzotriazole CAS: 3147-75-9 Molecular Formula: C <sub>20</sub> H <sub>25</sub> N <sub>3</sub> O Purity: ≥ 99% Molecular Weight: 323.43 g/mol		Melting range 101 - 109 °C	PE, PP, PVC, ABS, Polycarbonate, Adhesives, Elastomers
EVERSTAB 360		2,2'-methylenebis(6-(2H-benzotriazol-2-yl)-4-(1,1,3,3-tetramethylbutyl)phenol) CAS: 103597-45-1 Molecular Formula: C <sub>41</sub> H <sub>50</sub> N <sub>6</sub> O <sub>2</sub> Purity: ≥ 98% Molecular Weight: 658.87 g/mol		Melting range 193 - 196 °C	Acrylic Resins, PET, Polycarbonate, PA, XPS/EPS, Rubber





### 1.2 BENZOATES

BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVERSTAB 120		2,4-di-tert-butylphenyl 3,5-di-tert-butyl-4-hydroxybenzoate CAS: 4221-80-1 Molecular Formula: C <sub>29</sub> H <sub>42</sub> O <sub>3</sub> Molecular Weight: 438.64 g/mol		Melting temperature 198 °C	Polyethylene, Polypropylene, Polystyrene, PU, TPU, Polypropylene Films, Coatings, Adhesives, Fiber
EVERSTAB 2908		Hexadecyl 3,5-bis-tert-butyl-4-hydroxybenzoate CAS: 67845-93-6 Molecular Formula: C <sub>31</sub> H <sub>54</sub> O <sub>3</sub> Purity: ≥ 99% Molecular Weight: 474.76 g/mol		Melting range 59 - 63 °C	Polyolefins, PP, TPO, PE (HDPE, LLDPE, LDPE) in Moldings, Films and Tapes



### 1.3 NICKEL QUENCHER

BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVERSTAB 1084		(butylamine)[[2,2-thiobis[4-(1,1,3,3-tetramethylbutyl)phenolato]](2-)-0,0',S]nickel CAS: 14516-71-3 Molecular Formula: C <sub>32</sub> H <sub>51</sub> NNiO <sub>2</sub> S Purity: ≥ 99% Molecular Weight: 572.54 g/mol		Melting range 245 - 280 °C	PP, PE Agricultural Films - Resistant to Pesticides (halogenated and sulphated)













### 1.4 TRIAZINES

BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVERSTAB 1164		2-(4,6-bis(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)phenol CAS: 2725-22-6 Molecular Formula: C <sub>33</sub> H <sub>39</sub> N <sub>3</sub> O <sub>2</sub> Purity: ≥ 98,5% Molecular Weight: 509.68 g/mol		Melting range 88 - 91 °C	Greenhouses PE Films, Synthetic Fibres (PP, PA, PET), Engineering Resins Like PA, PC, PET, PBT, PMMA, POM, PE, PP, TPO, ASA, ABS
EVERSTAB 1577		2-(diphenyl-1,3,5-triazin-2-yl)-5-(hexyloxy)phenol CAS: 147315-50-2 Molecular Formula: C <sub>27</sub> H <sub>27</sub> N <sub>3</sub> O <sub>2</sub> Purity: ≥ 99% Molecular Weight: 425.52 g/mol		Melting range 147 - 151 °C	Polycarbonates, Polyesters, Resins







### 1.5 BENZOPHENONES

BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVERSTAB B81		[2-hydroxy-4-(octyloxy)phenyl](phenyl)methanone CAS: 1843-05-6 Molecular Formula: C <sub>21</sub> H <sub>26</sub> O <sub>3</sub> Purity: ≥ 99% Molecular Weight: 326.43 g/mol		Melting range 47 - 49 °C	Polyolefins Especially for Films Used in Agricultural Applications, Plasticized PVC and Coating

## 1.6 HALS

















BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVERSTAB 119		N,N',N'',N'''-tetrakis(4,6-s-(butyl-(N-methyl-2,2,6,6-tetramethylpiperidin-4-yl)amino)triazin-2-yl)-4,7-diazadecane-1,10-diamine CAS: 106990-43-6 Molecular Formula: C132H250N32 Purity: ≥ 99% Molecular Weight: 2285.60 g/mol		Melting range 115 - 150 °C	Polyolefins, Polypropylene Fibers and Polyethylene-based Agricultural Films, Styrenic Polymers (ABS, ASA), Polyamides (especially fibers), TPU, Polyacetal and Powder Coating
EVERSTAB 292		Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 Purity: ≥ 96%		Viscosity (20 °C) 450 cP	Coatings, Acrylics, Alkyds and Polyesters, Styrene, Acrylics, PP, PE, Unsaturated Polyesters, Polyurethane, Elastomers and Vinyl Monomers (PVB and PVC)
EVERSTAB 622		Butanedioic acid, 1,4-dimethyl ester, polymer with 4-hydroxy-2,2,6,6-tetramethyl-1-piperidineethanol CAS: 65447-77-0 Repeating Unit Formula: (C14H25O4N)n Molecular Weight: 3100-4000 g/mol		Softening range 50 - 70 °C	Polyolefins, POM, PMMA, PA, PU, UPES, TS, Powder for Coatings, Plasticized PVC, SBS, SIS, Hot Melt Adhesives, Fibers
EVERSTAB 770		Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate CAS: 52829-07-9 Molecular Formula: C28H52N2O4 Purity: ≥ 99% Molecular Weight: 480.72 g/mol		Melting range 80 - 86 °C	PP, TPO, PS, HIPS, SAN, ASA, ABS, PU, PA, Polyacetals
EVERSTAB 944		1,6-Hexanediamine, N1,N6-bis(2,2,6,6-tetramethyl-4-piperidyl)-, polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products with 2,4,4-trimethyl-2-pentanamine CAS: 70624-18-9 Molecular Weight: 2100-3000 g/mol		Melting range 100 - 135 °C	Polyolefins, PU, PVC, PA, POM
EVERSTAB 3346		1,6-Hexanediamine, N1,N6-bis(2,2,6,6-tetramethyl-4-piperidyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine CAS: 82451-48-7 Repeating Unit Formula: (C31H56N8O)n Molecular Weight: 1450-1750 g/mol		Melting range 110 - 130 °C	PE, PP, PS, PA, PU, Flexible PVC, Rigid PVC, Synthetic Elastomer, Adhesive

## 1.7 CYANOACRILATE

BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVERSTAB 309		N-(4-ethoxycarbonylphenyl)-N'-methyl-N'-phenylformamide CAS: 6197-30-4 Molecular Formula: C24H27NO2 Molecular Weight: 361.48 g/mol Purity: ≥ 95%		Melting temperature -10 °C	PVC plastisol, PVC-p, Polyester, PMMA, Silicone Emulsions, Liquid Inks, Acrylic, Vinyl Adhesives, Acrylic Resins, Urea-Formaldehyde Resins, Alkyd Resins, Epoxy Resins, Cellulose Nitrate, PUR Systems, Oil Paints, Polymer Dispersions
EVERSTAB 305		Ethyl 2-cyano-3,3-diphenylacrylate CAS: 5232-99-5 Molecular Formula: C18H15NO2 Molecular Weight: 277.31 g/mol Purity: ≥ 99%		Melting range 97-99 °C	PA, PVC, Polyester and Polystyrene copolymer, Acrylic and Polyurethane coatings, Gel coatings, Inks, Acrylic and Vinyl Adhesive, Etc.
EVERSTAB 303		Pentaerythritol tetrakis(2-Cyano-3,3-Diphenylacrylate) CAS: 178671-58-4 Molecular Formula: C69H48N4O8 Molecular Weight: 1061.14 g/mol Purity: ≥ 99%		Melting range 174 - 178 °C	Used for ABS, ASA, PC, etc.







## 2. ANTIOXIDANTS

### 2.1 PHENOLICS



BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVEROX 245		Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate] CAS: 36443-68-2 Molecular Formula: C34H50O8 Molecular Weight: 586.8 g/mol		Melting range 76 - 79 °C	Impact-modified PS, ABS, MBS, SB, SBR-latexes, POM Homoand Copolymers, PU, PA, Thermoplastic Polyesters, PVC and Other Polymers
EVEROX 1010		Pentaerythritol tetrakis (3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) CAS: 6683-19-8 Molecular Formula: C73H108O12 Purity: ≥ 98% Molecular Weight: 1177.6 g/mol		Melting range 110 - 125 °C	Polyolefins Homo- and Copolymers, POM, PA, PES, PUR, PVC, HIPS, ABS, EPDM, Latex, SBS/SIS, IIR
EVEROX 1035		Thiodiethylene bis [3-(3,5-di-tert-butyl-4-Hydroxyphenyl)propionate] CAS: 41484-35-9 Molecular Formula: C38H58O6S Purity: ≥ 98% Molecular Weight: 642.9 g/mol		Melting range 63 - 82 °C	Wire and Cable Resin Containing Carbon Black, LDPE, XLPE Cable, HIPS, PP, ABS, Polyvinyl Acetate, Polyurethane Elastomer, Hot Melt Adhesive
EVEROX 1076		Octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate CAS: 2082-79-3 Molecular Formula: C35H62O3 Purity: ≥ 98% Molecular Weight: 530.86 g/mol		Melting range 50 - 55 °C	Waxes Plasticizers, Elastomers, Binder for Coating and "Offset" Printing Inks and for Thermoplastic Resins
EVEROX 1098		N,N'-hexane-1,6-diybis [3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionamide] CAS: 23128-74-7 Molecular Formula: C40H64N2O4 Purity: ≥ 98% Molecular Weight: 636.95 g/mol		Melting range 156 - 161 °C	Thermoplastic Resins, Synthetic Fibers, Elastomers, Hot Melt Adhesives, Aliphatic Polyamidic Resins, Polyacetals, Polyesters, Polyurethanes
EVEROX 1330		3,3',3'',5,5',5''-hexa-tert-butyl-α,α',α''-(mesitylene-2,4,6-triyl)tri-p-cresol CAS: 1709-70-2 Molecular Formula: C54H78O3 Purity: ≥ 98% Molecular Weight: 775.21 g/mol		Melting range 240 - 245 °C	PE, PP, Polybutene, Linear Polyesters, Polyamides, Styrene Homo- and Copolymers, PVC, Polyurethanes, Elastomers, Adhesives
EVEROX 2246		6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol CAS: 119-47-1 Molecular Formula: C23H32O2 Molecular Weight: 340.5 g/mol		Melting range 123 - 128 °C	PE, PP, ABS, PVC, Rubber
EVEROX 3114		1,3,5-tris(3,5-di-tert-butyl-4-hydroxybenzyl)-1,3,5-triazine-2,4,6-triyl-trione CAS: 27676-62-6 Molecular Formula: C48H69N3O6 Molecular Weight: 784.08 g/mol		Melting range 218 - 219 °C	Polyolefins, Polypropylene Fiber and Films, Polypropylene or Propylene-olefin Copolymer (PP)









## 2.2 THIOESTERS

BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVEROX 1800		Didodecyl 3,3'-thiodipropionate CAS: 123-28-4 Molecular Formula: C <sub>30</sub> H <sub>58</sub> O <sub>4</sub> S Purity: ≥ 93% Molecular Weight: 514.84 g/mol		Melting range 39 - 42 °C	PE and Polyolefin, PVC, Acrylic Resins, ABS Resins, Other Plastic Materials, Lubricant Oils
EVEROX 1801		Di(tridecyl) 3,3'-thiodipropionate CAS: 10595-72-9 Molecular Formula: C <sub>32</sub> H <sub>62</sub> O <sub>4</sub> S Purity: ≥ 93% Molecular Weight: 542.89 g/mol		Viscosity (25 °C) 55 cP	Polystyrene, ABS, Rubbers
EVEROX 1802		Diocetadecyl 3,3'-thiodipropionate CAS: 693-36-7 Molecular Formula: C <sub>42</sub> H <sub>82</sub> O <sub>4</sub> S Purity: ≥ 93% Molecular Weight: 683.16 g/mol		Melting range 63 - 70 °C	Polyolefins, TPE, Styrene Copolymers (ABS, MBS)

## 2.3 METAL DEACTIVATOR

BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVEROX 1024		2,3-bis[[3-[3,5-di-tert-butyl-4-hydroxyphenyl]propionyl]] propionohydrazide CAS: 32687-78-8 Molecular Formula: C <sub>34</sub> H <sub>52</sub> N <sub>2</sub> O <sub>4</sub> Purity: ≥ 98% Molecular Weight: 552.79 g/mol		Melting range 221 - 232 °C	Elastomers and Polyolefins, PA, TPU

## 2.4 PHOSPHITES

BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVEROX 626		3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa- -3,9-diphosphaspiro[5.5]undecane CAS: 26741-53-7 Molecular Formula: C <sub>33</sub> H <sub>50</sub> O <sub>6</sub> P <sub>2</sub> Purity: ≥ 95% Molecular Weight: 604.69 g/mol		Melting range 170 - 180 °C	PE, PP, PS, PA, PC, ABS
EVEROX 1680		Tris(2,4-di-tertbutylphenyl) phosphite CAS: 31570-04-4 Molecular Formula: C <sub>42</sub> H <sub>63</sub> O <sub>3</sub> P Purity: ≥ 99% Molecular Weight: 646.921 g/mol		Melting range 183 - 187 °C	Polyolefins, Styrene Homoand Co-Polymers, TPE, Hot Melt Adhesives
EVEROX TPP		Triphenyl phosphite CAS: 101-02-0 Molecular Formula: C <sub>18</sub> H <sub>15</sub> O <sub>3</sub> P Molecular Weight: 310.29 g/mol		/	PVC, PP, PS, Polyacetate, ABS, Epoxy Resin, Unsaturated Polyester Resin, etc.



### 3. BLENDS





Are also available blends of Antioxidants (like EVEROX B215, EVEROX B225, EVEROX B900, etc.) and blends of UV-Stabilizers/HALS (like EVERSTAB 783, 791, etc.).

Phenol-Phosphite blends are available upon request.

**If you don't find the desired product in this product guide, don't hesitate to contact us by phone or mail.**







**We are at your disposal to find the proper solution to all your needs.**

### 4. OPTICAL BRIGHTENER










BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVERFLUORESCENT OB		2,5-thiophenediylbis(5-tert-butyl-1,3-benzoxazole) CAS: 7128-64-5 Molecular Formula: C <sub>26</sub> H <sub>26</sub> N <sub>2</sub> O <sub>2</sub> S Molecular Weight: 430.56 g/mol Purity: ≥99%		Melting Point 201 °C	Suitable for PVC formulation when a bright color is required. Also used in Paints, Clear Coats, Pigments, Paper Industry, etc.
EVERFLUORESCENT OB ONE		2,2'-(vinylenedi-p-phenylene)bisbenzoxazole CAS: 1533-45-5 Molecular Formula: C <sub>28</sub> H <sub>18</sub> N <sub>2</sub> O <sub>2</sub> Molecular Weight: 414.46 g/mol Purity: ≥98%		Melting Point 357 °C	Can be used as disperse dye in the chemical fibre, and likeoil dissolving colouring agent in plastics, whitening agent for polyester melt, etc.

### 5. BLOWING AGENTS

BLOWING AGENTS - Dedicated brochure available

BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
EVERFOAM SERIES		C,C'-azodi(formamide) CAS: 123-77-3 Molecular Formula: C <sub>2</sub> H <sub>4</sub> N <sub>4</sub> O <sub>2</sub> Purity: ≥ 97% Molecular Weight: 116.08 g/mol		Decomposition temperature ≥ 200 °C	PVC, PS, PE, PP, EVA, TPR, Rubber
EVERFOAM OBESH SERIES		4,4'-oxydi(benzenesulphonohydrazide) CAS: 80-51-3 Molecular Formula: C <sub>12</sub> H <sub>14</sub> N <sub>4</sub> O <sub>5</sub> S <sub>2</sub> Purity: > 86% Molecular Weight: 358.39 g/mol		Decomposition temperature ≥ 155 °C	Rigid and Flexible PVC, Rubber, Thermoplastic and Thermosetting Resins
EVERFOAM AZDN		2,2'-dimethyl-2,2'-azodipropionitrile CAS: 78-67-1 Molecular Formula: C <sub>8</sub> H <sub>12</sub> N <sub>4</sub> Purity: ≥ 99% Molecular Weight: 164.21 g/mol		Melting range 99 - 104 °C	PVC, Rubber

## 6. OTHERS

BRAND NAME	STOCK	CHEMICAL NAME	CHEMICAL STRUCTURE	PROPERTIES	APPLICATION AND USE
<b>EVERTITAN SERIES</b>		Titanium dioxide CAS: 13463-67-7 Molecular Formula: TiO <sub>2</sub> Molecular Weight: 79.87 g/mol	$O=Ti=O$	-	PVC, PS, PE, PP, EVA, TPR, Rubber
<b>DOTP</b>		1,4-bis(2-ethylhexyl) benzene-1,4-dicarboxylate CAS: 6422-86-2 Molecular Formula: C <sub>24</sub> H <sub>38</sub> O <sub>4</sub> Purity: ≥ 99% Molecular Weight: 390.56 g/mol		Viscosity (25 °C) 66 cP	PVC, Rubber
<b>DINP</b>		Diisononyl phthalate CAS: 28553-12-0 Molecular Formula: C <sub>26</sub> H <sub>42</sub> O <sub>4</sub> Purity: ≥ 99% Molecular Weight: 418.61 g/mol		Viscosity (20 °C) 72 - 82 cP	PVC, Rubbers, Paints, Adhesives
<b>EPOXIDIZED SOYBEAN OIL (ESO)</b>		Soybean oil, epoxidized CAS: 8013-07-8		Viscosity (25 °C) 350 - 650 cP	PVC, Paint, Coatings, Adhesives
<b>EVK AMS DIMER</b>		2,4-diphenyl-4-methyl-1-pentene CAS: 6362-80-7 Molecular Formula: C <sub>18</sub> H <sub>20</sub> Purity: ≥ 92% Molecular Weight: 236.34 g/mol		Viscosity (20 °C) 18 cP	PS, ABS, AS, EPS, Rubber, Coating, PE



Available on the Italian Stock - Prompt Delivery



Available upon request

## DISCLAIMER

Tutte le informazioni e i dati contenuti nel presente documento (nel prosieguo le "Informazioni") sono stati elaborati in modo accurato sulla base delle conoscenze attuali di Everkem S.r.l. e sono forniti esclusivamente a mero scopo illustrativo delle caratteristiche di qualsivoglia prodotto indicato nel presente documento (nel prosieguo il "Prodotto"). L'obbligo di verifica e decisione dell'applicabilità di questi prodotti per un utilizzo specifico rimane ad esclusiva responsabilità dell'utilizzatore e non può essere sostituita da tali informazioni. È responsabilità dell'acquirente e/o utilizzatore analizzare debitamente le schede tecniche di sicurezza di qualsivoglia Prodotto, verificare la correttezza delle Informazioni e valutare se la commercializzazione o lo sfruttamento del Prodotto singolarmente, o contenuto in formulazioni, utilizzato come additivo, unito ad altri prodotti, o destinato ad altre lavorazioni industriali sia, in concreto, in base all'utilizzo specifico che intende farne, conforme alle disposizioni di legge applicabili e che non violi, direttamente o indirettamente, diritti di proprietà intellettuale o di privativa industriale di terzi (quali, ad esempio, brevetti, marchi o modelli di utilità). Everkem S.r.l., pertanto, declina ogni responsabilità nel caso in cui l'utilizzo o lo sfruttamento commerciale in qualsivoglia modo e per qualsivoglia finalità del Prodotto cagioni eventuali danni a persone o a cose e, in particolare, se: a) le Informazioni siano errate o incomplete, b) il Prodotto venga utilizzato in modo contrario o non conforme alle indicazioni fornite dal venditore o dal produttore del Prodotto o dalle relative schede tecniche di sicurezza del Prodotto o in violazione delle Condizioni Generali di Vendita presenti sul sito di Everkem S.r.l. al seguente link <https://everkem.it/wp-content/uploads/2021/01/CONDIZIONI-DI-VENDITA-EVERKEM-ITA-EN-2021.pdf> e c) violi diritti di proprietà intellettuale o industriale di terzi.

All information and data contained herein (hereinafter only the "Information") have been carefully filled to the best of Everkem S.r.l.'s current knowledge and are provided solely to describe the characteristics of any product pointed out herein (hereinafter only the "Product"). It does not release you to verify within the scope of your liability, whether the products are suitable for the intended application. It is exclusive responsibility of the purchaser and/or user to duly analyze the safety data sheets of any Product, to verify the correctness of the Information and to assess whether the marketing or exploitation of the Product as it is, or formulated or contained in other products, used as an additive or for other processing or industrial uses is, in concrete terms and according to the specific use it intends to make of it, in compliance with the applicable laws and that it does not infringe, directly or indirectly, any third parties' intellectual property rights or industrial property rights (such as, for example, patents, trademarks or utility models). Therefore, Everkem S.r.l., disclaims its liability in the event the use or commercial exploitation in any way whatsoever and for any purpose of the Product causes any damage to persons or property and, in particular, if: a) the Information is incorrect or incomplete, b) the purchaser exploited the Product without complying with the indications provided by the seller or by the manufacturer of the Product or by the safety data sheets of the Product or in violation of the Sale General Terms and Conditions published on Everkem S.r.l.'s web page at the following link <https://everkem.it/wp-content/uploads/2021/01/CONDIZIONI-DI-VENDITA-EVERKEM-ITA-EN-2021.pdf> and c) infringes intellectual or industrial property rights of third parties.





**EVERKEM s.r.l.**

**Head office**

Via Gioacchino Murat, 23  
20159 Milano - ITALY  
P. +39 02 67076513  
F. +39 02 67076516  
info@everkem.it

**Registered office**

Via della Lirica, 11  
48124 Ravenna - ITALY

**Administration**

Corso Mazzini, 140  
48022 Lugo (RA) - ITALY

**Logistics**

Via Groane, 2  
20811 Cesano Maderno (MI) - ITALY

Via Stradone, 88  
48022 San Bernardino di Lugo (RA) - ITALY

Via Piero Achille, 4  
26838 Tavazzano con Villavesco (LO) - ITALY

**everkem.com**

